

^ Overview

Dimensions	Without mount: Ø90 x 152.5 mm (Ø3.5 x 6")
	With mount: 90 x 94 x 179.5 mm (3.5 x 3.7 x 7")
IR Night Vision	20 m (65 ft)
Zoom Mode	2x Optical
Smart Detections (People, Vehicles, Animals)	✓
Resolution	2K
Field of View	Wide: H: 99.7°, V: 51.9°, D: 121° Tele: H: 45.5°, V: 25.4°, D: 52.4°
Pan-Tilt Range	Pan: 350° Tilt: 100°
Audio	Microphone
Weatherproofing	IP66
Tamper Resistance	IK04
Mounting	Wall mount, pole mount (Included) Conduit adapter, surface, in-ceiling, pendant, corner mount (Optional)

^ Performance

Networking Interface	10/100 MbE RJ45 port
----------------------	----------------------

Video

Max. Frame Rate	30 FPS
Resolution	4MP 2688 x 1512 (16:9)

Optics

Sensor	5MP 1/2.7" CMOS
Lens	F 3.42–6.85 mm; <i>f</i> /1.85– <i>f</i> /2.4

Night Mode

Built-in IR & white LED illumination with IR cut filter

^ **Hardware**

Max. Power Consumption	14W
Supported Voltage Range	37—57V DC
Power Method	PoE+
Pole Mount Diameter	1.5–2" (38–50 mm)
Weight	Without mount: 580 g (1.3 lb) With mount: 650 g (1.4 lb)
Enclosure Material	Aluminum alloy, polycarbonate
Mount Material	Wall mount: polycarbonate Pole mount: aluminum alloy
Button	(1) Factory-reset
Ambient Operating Temperature	-30 to 45° C (-22 to 113° F)
Ambient Operating Humidity	0 to 90% noncondensing
NDAA Compliant	✓
Certifications	CE, FCC, IC